



Specification		
Model	SS-2.56	
Casing	Material: SUS 304 Thickness: 2.0mm	
Rotating Shaft	Material: SUS 304	
Screen	Flow Passage Width	236mm
	Rotating Oval Plates	6 rows (Material: SUS301-CSP t0.5)
	Gap	1.0mm
Drive Unit	Gear Motor	
	3φ 200V 0.1kw 1unit	
	Reduction Gear Ratio 1/150	
	Revolution Speed 9.67r/min(50Hz), 11.7r/min(60Hz)	
	Rated Current Value 0.69A(50Hz), 0.6A(60Hz)	
Class E Insulation, TEFC Outdoor Type		
Painting Colour : Manufacturer Standard		
Approx. Weight	50kg	

Caution: Do not reverse the motor rotation.

Drawing for Reference

The drawing is for reference only and subject to change without notice.

	-	.	-	製図	-	-		品番/ITEM NO.	型式/MODEL	図面名称/DRAWING NAME	装置名称/UNIT NAME	単位	尺度	サイズ	変更回数
	-	.	-	DRAWING	-	-		-	SS-2.56	Outline Drawing	Thickening Model	mm	1:5	A3	△
	-	.	-	設計	-	-		工番/JOB NO.	図面番号/DRAWING NO.	御客様社名/CLIENT	投影法	年月日	DATE	2021-01-06	
	-	.	-	CHECKED	-	-		-	-	-	第一角	-	-	-	
記号	年月日	記事	訂正者	承認	-	-	株式会社	研電社		KENDENSHA Co.,Ltd		2021-01-06			
MARK	DATE	CONTENT	REVISED	APPROVED	-	-									